

[54] SPORT SHOE TREAD

4,085,526 4/1978 Hemmer 36/59 R

[76] Inventor: Armin A. Dassler, Ringstrasse 121,
D-8522 Herzogenaurach, Fed. Rep.
of Germany

FOREIGN PATENT DOCUMENTS

836899 4/1952 Fed. Rep. of Germany 36/59 R
19362 of 1904 United Kingdom 36/59 A

[21] Appl. No.: 941,589

[22] Filed: Sep. 12, 1978

~~Primary Examiner James Kee Chi~~
~~Attorney, Agent, or Firm—Craig & Antonelli~~

[30] Foreign Application Priority Data

Sep. 12, 1977 [DE] Fed. Rep. of Germany ... 7728190[U]

[51] Int. Cl.² A43B 23/28; A43C 15/02

[52] U.S. Cl. 36/59 R; 36/59 A;
36/59 C; 36/30 R

[58] Field of Search 36/59 R, 59 A, 59 C,
36/30 R, 67 R, 67 A, 67 B, 129, 114

[56] References Cited

U.S. PATENT DOCUMENTS

1,176,647 3/1916 Bucolo 36/59 A
1,697,019 1/1929 Pickering 36/59 R
1,704,187 3/1929 Glidden et al. 36/30 R
1,846,450 2/1932 Packard 36/59 C

[57] ABSTRACT

A tread for a sport shoe which includes a sole having projections extending outwardly from a tread surface. The tread includes a one-piece, thin-walled, metal part with at least two separate, dimensionally reinforced surface sections bearing the integrally molded projections. The reinforced surface sections may include a plurality of embossed, smooth-surfaced and/or bevelled projections. The metal part is fixedly attached to an inner surface of the shoe sole by either a thin wire grid embedded in the synthetic resin sole or uniformly distributed perforations.

5 Claims, 2 Drawing Figures

